

RECEIVED
CENTRAL FAX CENTER
JUL 26 2006

Amendments to the Claims:

Claims 8, 16, 19 and 21 are amended and claim 22 is added as set forth hereinafter.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Cancelled).

2. (Previously Presented) The portable handheld work apparatus arrangement of claim 5, wherein said first strut defines an axis of rotation at said first end thereof; said first and second attachment points are at first and second distances (a, b) from said axis of rotation; and, said first and second distances (a, b) are different from each other.

3. (Previously Presented) The portable handheld work apparatus arrangement of claim 5, wherein said work apparatus has a frame and said transport wheel is disposed at said frame when said second strut is fixed at said first attachment point.

4. (Original) The portable handheld work apparatus arrangement of claim 3, wherein said transport wheel is at a distance (c, c') from said frame when said second strut is fixed at said second attachment point.

5. (Previously Presented) A portable handheld work apparatus arrangement comprising:

a work apparatus including a drive motor and a work tool driven by said drive motor;

5 at least one transport wheel;

first and second struts for connecting said transport wheel to said work apparatus;

said first strut having a first end facing away from said transport wheel and said first strut being rotatably mounted on
10 said work apparatus at said first end;

said second strut having a first end facing away from said transport wheel;

said second strut being fixable at said first end thereof on said work apparatus at at least first and second attachment
15 points thereon so as to change the position of said transport wheel relative to said work apparatus; and,

said attachment points being configured as respective detent recesses.

6. (Original) The portable handheld work apparatus arrangement of claim 5, wherein said first attachment point is configured as a detent recess closed toward said second strut.

7. (Original) The portable handheld work apparatus arrangement of claim 6, wherein said second attachment point is configured as a detent recess open toward said second strut.

8. (Currently Amended) ~~The portable handheld work apparatus~~

~~arrangement of claim 7, further comprising~~ A portable handheld work apparatus arrangement comprising:

a work apparatus including a drive motor and a work tool
5 driven by said drive motor;

at least one transport wheel;

first and second struts for connecting said transport wheel
to said work apparatus;

said first strut having a first end facing away from said
10 transport wheel and said first strut being rotatably mounted on
said work apparatus at said first end;

said second strut having a first end facing away from said
transport wheel;

said second strut being fixable at said first end thereof on
15 said work apparatus at at least first and second attachment
points thereon so as to change the position of said transport
wheel relative to said work apparatus;

said attachment points being configured as respective detent
recesses;

20 said first attachment point being configured as a detent
recess closed toward said second strut;

said second attachment point being configured as a detent
recess open toward said second strut;

a bolt extending transversely to said second strut; and,
25 said bolt coacting with said first and second detent
recesses to fix said transport wheel in position relative to said
frame.

9. (Original) The portable handheld work apparatus arrangement

of claim 8, further comprising a fixing screw coacting with said bolt to releasably fix said second strut in one of said detent recesses.

10. (Original) The portable handheld work apparatus arrangement of claim 9, further comprising a rail fixedly connected to said work apparatus and said detent recesses being formed in said rail.

11. (Original) The portable handheld work apparatus arrangement of claim 9, further comprising a rail; and, said rail and said first strut being releasably fixed on said work apparatus.

12. (Previously Presented) The portable handheld work apparatus arrangement of claim 5, further comprising attachment points in addition to said second attachment point to define a plurality of second attachment points at respectively different distances from said axis of rotation at said first end of said first strut.

13. (Previously Presented) The portable handheld work apparatus arrangement of claim 5, wherein said transport wheel is a first transport wheel and said arrangement further comprises a second transport wheel and an axle common to said first and second transport wheels; an additional first strut; and, said axle is held by said two first struts and said second strut.

14. (Previously Presented) The portable handheld work apparatus arrangement of claim 5, wherein said work apparatus is a sweeper

or motorized cultivator.

15. (Cancelled).

16. (Currently Amended) A transport device for a portable handheld work apparatus, the transport device comprising:

at least one transport wheel;

first and second struts connected to said transport wheel;

5 said second strut having a first end facing away from said transport wheel;

a rail arranged on said first end of said second strut and said rail having at least two attachment points; and,

10 a fixing screw for fixing said second strut to said rail at said second end of said second strut; and,

said attachment points being configured as detent recesses.

17. (Previously Presented) The transport device of claim 16, wherein said first strut has a first end facing away from said transport wheel; and, wherein said transport device further comprises a bolt arranged at said first end of said first strut.

18. (Previously Presented) A transport device for a portable handheld work apparatus, the transport device comprising:

at least one transport wheel;

first and second struts connected to said transport wheel;

5 said second strut having a first end facing away from said transport wheel;

a rail arranged on said first end of said second strut and

said rail having at least two attachment points; and,

10 said rail having a detent recess formed therein closed in a
direction toward said second strut.

19. (Currently Amended) A transport device for a portable
handheld work apparatus, the transport device comprising:

at least one transport wheel;

first and second struts connected to said transport wheel;

5 said second strut having a first end facing away from said
transport wheel;

a rail arranged on said first end of said second strut and
said rail having at least two attachment points; and,

10 said rail having a plurality of detent recesses formed
therein open toward said second ~~strut~~ strut; and,

a bolt mounted on said second strut for coacting with said
detent recesses and said bolt extending transversely to said
second strut.

20. (Cancelled).

21. (Currently Amended) A portable handheld work apparatus
arrangement comprising:

a work apparatus including a drive motor and a work tool
driven by said drive motor;

5 at least one transport wheel for moving said work apparatus
over ground;

first and second struts for connecting said transport wheel
to said work apparatus;

10 said first strut having a first end facing away from said transport wheel and said first strut being rotatably mounted on said work apparatus at said first end;

said second strut having a first end facing away from said transport wheel;

15 said second strut being fixable at said first end thereof on said work apparatus at at least first and second attachment points thereon so as to change the position of said transport wheel relative to said work apparatus; ~~and,~~

20 said work apparatus having a frame and said transport wheel ~~[[is]]~~ being disposed at said frame when said second strut is fixed at said first attachment point so as to cause said transport wheel not to come into engagement with the ground when said work tool is in its work ~~position~~ position;

two handle tubes having respective handles and being connected to said work apparatus; and,

25 a carrier handle attached to said work apparatus between said drive motor and said two handle tubes.

22. (New) A portable handheld work apparatus arrangement comprising:

a work apparatus including a drive motor and a work tool driven by said drive motor;

5 at least one transport wheel;

first and second struts for connecting said transport wheel to said work apparatus;

said first strut having a first end facing away from said transport wheel and said first strut being rotatably mounted on

10 said work apparatus at said first end;

said second strut having a first end facing away from said transport wheel;

said second strut being fixable at said first end thereof on said work apparatus at at least first and second attachment

15 points thereon so as to change the position of said transport wheel relative to said work apparatus;

said attachment points being configured as respective detent recesses; and,

a bolt mounted on said second strut for coacting with said
20 detent recesses and said bolt extending transversely to said second strut.